



# MULTI-FREQUENCY, MULTI-GNSS ANTENNA



The A65 GNSS antenna is engineered to deliver millimeter level accuracy for both land and marine applications. It supports current and future GNSS signals, including GPS, GLONASS, BeiDou, and Galileo, ensuring long-term reliability.

As a multi-GNSS precision antenna, the A65 is ideal for surveys, RTK positioning and navigation, precise guidance, and machine control. Designed for challenging environments—such as near buildings and foliage—the A65 provides superior multipath mitigation, a stable phase center, and strong signal-to-noise ratios (SNR), even at low elevations. Built for durability, the ruggedized housing features an aluminum base designed to withstand salt, fog, and spray in marine environments. The antenna exceeds durability standards, passing the two-meter pole drop test with ease.

### GNSS Receiver Specifications

**Receiver Type:** GNSS Sensor  
**Signals Received:** GPS L1/L2/L5, GLONASS G1/G2, BeiDou B1/B2/B3, SBAS, L-band, and Galileo E1/E5a/E5b/E6  
**GNSS Frequency:** 1.164 to 1.300 GHz  
 1.539 to 1.606 GHz  
**LNA Gain:** 30 dBn  
**LNA Noise:** 2.5 dB, typical

### L-Band Sensor

**L-Band**  
**Frequency:** 1.539 - 1.559 GHz operation  
**L-Band LNA Gain:** 30 dB

### Power

**Input Voltage:** 2.5 to 15 VDC  
**Input Current:** 17 mA, typical

### Mechanical

**Enclosure:** Aluminum base with Lexan™ plastic cap  
**Dimensions:** 4.1 H x 15.7 D (cm)  
 1.6 H x 6.2 D (in)  
**Weight:** 0.40 kg (0.88 lbs)  
**Mount:** 5/8 inch female thread  
**RF Connector:** TNC (straight)

### Environmental

**Storage Temperature:** -40° C to +95° C (-40°F to +203°F)  
**Operating Temperature:** -40° C to +85° C (-40°F to +185°F)  
**Enclosure Rating:** IP69K  
**Shock/Vibration:** EP455

### Hemisphere GNSS

1700 N. Desert Drive, Suite 101  
 Tempe, AZ 85288, USA

Phone: +1 (480) 348-6380  
 Toll-Free: +1 (855) 203-1770  
 Fax: +1 (480) 270-5070

precision@hgns.com  
 hgns.com